

دوربین های تحت شبکه سری اسمارت تیتانیوم

Smart Titanium Series IP Camera



دوربین های سری هوشمند تیتانیوم کی دی تی با گارانتی طلایی ۵ ساله خود بهترین انتخاب برای حرفه ای ها می باشد.

برتری ها:

- دارای وب کاملا فارسی
 - نرم افزارهای کاملا فارسی
 - دارای سرور P2P در پارس آنلاین
 - امنیت بسیار بالا و محافظت شده از هکرها
 - پشتیبانی از سه استریم همزمان
 - پشتیبانی از Onvif در ۲ نسخه 2.6 و Profile S
 - پشتیبانی از تمام قابلیت های WDR/HLC/ BLC
 - پشتیبانی از ۸ ناحیه ROI
 - پشتیبانی از Nas Storage
 - دارای ورودی و خروجی صدا بصورت استاندارد در تمام مدلها
 - پشتیبانی از کارت حافظه بصورت استاندارد در تمام مدلها
 - سیستم دید در شب حساس به فاصله ها و بسیار هوشمند
 - استفاده از سنسور سونی استار لایت در تمامی مدلها
 - دارای لنزهای متور ایز در مدلهای وریفوکال
 - عملکرد تنظیمات تصویر بر اساس بازه زمانی
 - عملکرد تنظیمات تصویر بر اساس روز و شب
 - **Multicast Support**
 - قابلیت کار در دمای -30 و +70
- قابلیت های هوشمند:
 - قابلیت هوشمند پارک ممنوع
 - قابلیت هوشمند عبور از خط
 - قابلیت هوشمند فنس مجازی
 - قابلیت هوشمند تشخیص سرعت غیر مجاز
 - قابلیت هوشمند گم شدن اشیا
 - قابلیت هوشمند اضافه شدن اشیا
 - قابلیت هوشمند شمارش افراد در هنگام ورود
 - قابلیت هوشمند شمارش افراد در هنگام خروج
 - قابلیت هوشمند توقف بیش از حد مجاز
 - قابلیت هوشمند پرسه زدن در محیط
 - قابلیت هوشمند تجمع غیر مجاز

1 KI-D35XL20F



DESCRIPTION

- **2 Mega Pixel Sony Starlight** CMOS Sensor
- **H.264+ / H.265+**
- 1920*1080P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 10 Meter IRcut Night Vision
- 2.8mm **Fixed Lens**
- DWDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66, IK10**
- 3-Axis Design
- DC12V/ POELAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 106.6X51.1mm
- Gross Weight: 320g
- Metal Housing: White

2 KI-D45XL20F



DESCRIPTION

- **2 Mega Pixel Sony Starlight** CMOS Sensor
- **H.264+ / H.265+**
- 1920*1080P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 20 Meter IRcut Night Vision
- 3.6mm **Fixed Lens**
- DWDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66, IK10**
- 3-Axis Design
- DC12V/ POELAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 114.0X89.6mm
- Gross Weight: 500g
- Metal Housing: White

3 KI-B55XL20F



DESCRIPTION

- **2 Mega Pixel Sony Starlight** CMOS Sensor
- **H.264+ / H.265+**
- 1920*1080P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 30 Meter IRcut Night Vision
- 3.6mm **Fixed Lens**
- DWDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC
- **11 Smart Function**
- Onvif Profile S, CGI, SDK
- Weather Resistance: **IP66**
- 3-Axis cable built-in bracket
- DC12V/ POELAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 75.9X210.8mm
- Gross Weight: 750g
- Metal Housing: White

4 KI-D45XL30F



DESCRIPTION

- **3 Mega Pixel Sony Starlight CMOS Sensor**
- **H.264+ / H.265+**
- 1536*2048P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 20 Meter IRcut Night Vision
- 3.6mm **Fixed Lens**
- **Real WDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66, IK10**
- 3-Axis Design
- DC12V/ POELAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 114.0X89.6mm
- Gross Weight: 500g
- Metal Housing: White

5 KI-D45XL50F



DESCRIPTION

- **5 Mega Pixel Sony Starlight CMOS Sensor**
- **H.264+ / H.265+**
- 1944*2592P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 20 Meter IRcut Night Vision
- 3.6mm **Fixed Lens**
- **DWDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66, IK10**
- 3-Axis Design
- DC12V/ POELAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 114.0X89.6mm
- Gross Weight: 500g
- Metal Housing: White

6 KI-D45XL80F



DESCRIPTION

- **8 Mega Pixel Sony CMOS Sensor**
- **H.264+ / H.265+**
- 2304*3435P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 30 Meter IRcut Night Vision
- 3.6mm **Fixed Lens**
- **Real WDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66, IK10**
- 3-Axis Design
- DC12V/ POELAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 114.0X89.6mm
- Gross Weight: 500g
- Metal Housing: White

7 KI-D55XL30A



DESCRIPTION

- **3 Mega Pixel Sony Starlight CMOS Sensor**
- **H.264+ / H.265+**
- 1536*2048P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 30 Meter IRcut Night Vision
- 2.8-12mm **Motorized Lens**
- **Real WDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66, IK10**
- 3-Axis Design
- DC12V/ POELAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 140.5X119.3mm
- Gross Weight: 1200g
- Metal Housing: White

8 KI-D55XL50V



DESCRIPTION

- **5 Mega Pixel Sony Starlight CMOS Sensor**
- **H.264+ / H.265+**
- 1944*2592P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 30 Meter IRcut Night Vision
- 2.8-12mm **Varifocal Lens**
- **DWDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66, IK10**
- 3-Axis Design
- DC12V/ POELAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 140.5X119.3mm
- Gross Weight: 1200g
- Metal Housing: White

9 KI-D55XL80A



DESCRIPTION

- **8 Mega Pixel Sony CMOS Sensor**
- **H.264+ / H.265+**
- 2304*3435P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 30 Meter IRcut Night Vision
- 2.8-12mm **Motorized Lens**
- **Real WDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66, IK10**
- 3-Axis Design
- DC12V/ POELAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 114.0X89.6mm
- Gross Weight: 500g
- Metal Housing: White

10 KI-B55XL30F



DESCRIPTION

- **3 Mega Pixel Sony Starlight CMOS Sensor**
- **H.264+ / H.265+**
- 1536*2048P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 30 Meter IRcut Night Vision
- 3.6mm **Fixed Lens**
- **Real WDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66**
- 3-Axis cable built-in bracket
- DC12V/ POE LAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 75.9X210.8mm
- Gross Weight: 720g
- Metal Housing: White

11 KI-B55XL50F



DESCRIPTION

- **5 Mega Pixel Sony Starlight CMOS Sensor**
- **H.264+ / H.265+**
- 1944*2592P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 30 Meter IRcut Night Vision
- 3.6mm **Fixed Lens**
- DWDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC
- Line Crossing/ Area Intrusion Function
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66**
- 3-Axis cable built-in bracket
- DC12V/ POE LAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 75.9X210.8mm
- Gross Weight: 720g
- Metal Housing: White

12 KI-B55XL80F



DESCRIPTION

- **8 Mega Pixel Sony Starlight CMOS Sensor**
- **H.264+ / H.265+**
- 2304*3435P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 30 Meter IRcut Night Vision
- 3.6mm **Fixed Lens**
- **Real WDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66**
- 3-Axis cable built-in bracket
- DC12V/ POE LAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 114.0X89.6mm
- Gross Weight: 500g
- Metal Housing: White

13 KI-B75XL30A



DESCRIPTION

- **3 Mega Pixel Sony Starlight CMOS Sensor**
- **H.264+ / H.265+**
- 1536*2048P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 50 Meter IRcut Night Vision
- 2.8-12mm **Motorized Lens**
- **Real WDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66**
- 3-Axis cable built-in bracket
- DC12V/ POE LAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 103.7X275.8mm
- Gross Weight: 1188g
- Metal Housing: White

14 KI-B75XL50V



DESCRIPTION

- **5 Mega Pixel Sony Starlight CMOS Sensor**
- **H.264+ / H.265+**
- 1944*2592P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 50 Meter IRcut Night Vision
- 2.8-12mm **Varifocal Lens**
- DWDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66**
- 3-Axis cable built-in bracket
- DC12V/ POE LAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 103.7X275.8mm
- Gross Weight: 1188g
- Metal Housing: White

15 KI-B75XL80A



DESCRIPTION

- **8 Mega Pixel Sony Starlight CMOS Sensor**
- **H.264+ / H.265+**
- 2304*3435P@30fps Max Resolution
- Tripple Stream Output
- Smart IR - SMD LED Technology
- Up To 30 Meter IRcut Night Vision
- 2.8-12mm **Motorized Lens**
- **Real WDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- **11 Smart Function**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66**
- 3-Axis cable built-in bracket
- DC12V/ POE LAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 114.0X89.6mm
- Gross Weight: 500g
- Metal Housing: White

16 KI-S150XL30V30



DESCRIPTION

- **3 Mega Pixel** Sony CMOS Sensor
- **H.264+ / H.265+**
- 1536*2048P@30fps Max Resolution
- Tripple Stream Output
- SMD LED Technology
- Up To 30 Meter IRcut Night Vision
- **30X Optical Zoom**
- **Real WDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- **Auto Tracking**
- Onvif 2.4/ Profile S/ CGI
- Weather Resistance: **IP66**
- 3-Axis cable built-in bracket
- DC12V/ 2way Audio/ SD Support /In-Out Alarm
- Wiper : Optional
- Gross Weight: 4.8kg

17 KI-LPR60A



DESCRIPTION

- **3 Mega Pixel** Sony CMOS Sensor
- **H.264+ / H.265+**
- 3MP@30fps / 1080P@60fps
- Dual stream support
- SMD LED Technology
- Up To 50 Meter IRcut Night Vision
- 9-22mm **Motorized Lens**
- **Real WDR/ 3D DNR/ ROI/ Defog/ P2P/ HLC/ BLC**
- Onvif 2.6/ Profile S/ CGI
- Weather Resistance: **IP66**
- 3-Axis cable built-in bracket
- DC12V/ POELAN/ 2way Audio/ SD Support /In-Out Alarm
- Size: \varnothing 110×84×231mm
- Gross Weight: 820g
- Metal Housing: White